

BUTLER-COTE™ FINISH SYSTEM

FOR BUTLER® BUILDING SYSTEMS



Butlerib® II Wall System
Cool Harvest

BUTLER-COTE™ FINISH SYSTEM

for Butler® Building Systems

All Butler-Cote™ fluoropolymer finishes have a Solar Reflectance Index of 29 or greater.

Standard stock availability varies by panel type, color, and gauge. Additional charges and minimum order quantity may apply.

			
Cool Solar White (A, B, C, D)	Cool Igloo White (C, D)	Cool Ivory White (B, C, D)	Cool Birch White (D)
			
Cool Shell Gray (A, B, C, D)	Cool Country Wheat (C, D)	Cool Desert Beige (C, D)	Cool Gray Stone (C)
			
Cool Emerald Green (A, B, C)	Cool Ocean Blue (B, C)	Cool Majestic Blue (C)	Cool Brick Red (B, C)
			
Cool Harvest (B, C, D)	Cool Onyx Black (Trim Only)	Cool Marsh Green (C)	Cool Palm Green
			
Cool Copper Penny (E)	Cool Metallic Silver (E)	Cool Jade Green (E)	Cool Bright Red (E)
			
Cool Parchment (E)	Cool Old Town Gray (E)		

ROOF PANEL GAUGE AVAILABILITY (Standard Stocked by Panel and Gauge)

- A Butlerib® II – 26 gauge (Cool Solar White Available in 24g)
- B MR-24® II – 24 gauge (Cool Solar White, Cool Shell Grey, and Cool Harvest Available in 22g)
- C VSR II™ – 24 gauge

WALL PANEL GAUGE AVAILABILITY (Standard Stocked by Type and Gauge)

Butlerib® II & Shadowall™ – 26 gauge StylWall® II Fluted – 24 gauge Trim – 26 gauge
StylWall® II Flat – 26 gauge MOD-36 – 22*, 24, 26, and 28* gauge

Insulated Metal Panels (IMP's) purchased through Butler are Available in Standard Butler-Cote™ Colors shown. Setup charges may apply.

- D Also available in 24 gauge for Butlerib® II, Shadowall™ and MOD-36
- E Not Standard Stocked for any panel type. Minimum Quantity Will Apply


* MOD-36 is only available in Galvalume and Interior White Finish for these gauges

All color selections are close representations, but are limited by processing and viewing conditions.

Lead times may vary by product selection. Contact your Butler Builder® for more information.

For color, gauges, or color/panel combinations not shown, additional charges apply and a minimum order is required.

MODULEZE™ II SOFFIT COLORS



Cool Solar White
24 ga.



Cool Ivory White
24 ga.



Cool Birch White
24 ga.



Cool Shell Gray
24 ga.




Cool Desert Beige
24 ga.



Cool Harvest
24 ga.

INTERIOR FINISH COLORS


Not Formulated for Exterior Use



Light Gray
Butlerib® II roof & wall,
StylWall® II Fluted,
Shadowwall™, MR-24®,
VSR II™ and MOD-36



Igloo White
Butler Thermawall™
& TextureWall™
— USDA-approved



Interior White
CMR-24® Liner and MOD-36
in 22 or 28 gauge only

COLOR AND GAUGE HAVE LIMITED AVAILABILITY BY PANEL TYPE AND MANUFACTURING LOCATION. EXTENDED LEAD-TIMES, SET UP CHARGES, AND LIMITED AVAILABILITY MAY OCCUR.

ENHANCE & PROTECT THE BEAUTY

The standard exterior paint finish for all Butler panels and trim is the Butler-Cote system, consisting of a full strength 70% Kynar 500® or Hylar 5000® PVDF resin-base fluoropolymer finish.

The Butler-Cote system resists the chalking and fading that often leaves a building looking drab and dated. Our 25-year warranty guarantees that, on roof and wall panel standard colors, chalking

will not exceed a rating of #8 and fading will not exceed 5ΔE color difference units. The warranty also covers peeling, cracks, or chipping of the paint finish.

While many manufacturers' warranties are prorated after a certain period of time, we offer our Butler-Cote roof and wall panel warranty for a full 25 years—with no prorating. It's a testament to our high performance standards.

Fluoropolymer Finish vs. Silicone Polyester After 8 Years of Weathering

Butler-Cote™ Fluoropolymer Finish		Industry Standard Silicone Polyester Coating
Original Color		
Level of Chalking Allowable Within Warranty Terms		
Warranty Period	25 years	10 years

A COMMITMENT TO BUILDING ENERGY EFFICIENCY

All standard Butler-Cote™ 25-year fluo-ropolymer color finishes feature a Solar Reflectance Index (SRI) of 29 or greater.

BUTLER-COTE™ FINISH SYSTEM SOLAR REFLECTANCE DATA			
Available Standard "Cool" Colors	Initial Solar Reflectance	Initial Emittance	Solar Reflectance Index (SRI)
Cool Solar White	0.76	0.84	93
Cool Igloo White	0.64	0.84	76
Cool Ivory White	0.63	0.83	74
Cool Birch White	0.64	0.84	77
Cool Shell Gray	0.55	0.84	63
Cool Country Wheat	0.61	0.84	72
Cool Desert Beige	0.49	0.84	55
Cool Gray Stone	0.37	0.85	39
Cool Marsh Green	0.34	0.85	35
Cool Emerald Green	0.30	0.85	30
Cool Palm Green	0.30	0.84	29
Cool Ocean Blue	0.33	0.84	33
Cool Majestic Blue	0.30	0.84	29
Cool Brick Red	0.34	0.85	35
Cool Harvest	0.32	0.84	32
Cool Onyx Black	0.30	0.84	29
Cool Metallic Silver	0.57	0.82	65
Cool Copper Penny	0.48	0.83	53
Cool Jade Green	0.29	0.86	29
Cool Bright Red	0.42	0.85	46
Cool Parchment	0.51	0.84	58
Cool Old Town Gray	0.40	0.85	43
Galvalume® Plus	0.70	0.84	84



Butler® building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Before finalizing project details, contact your nearest Butler Builder® or Butler Manufacturing™ for the latest information.

Kynar 500® is a registered trademark of Arkema. Hylar 5000® is a registered trademark of Solvay Solexis. USGBC logo is a registered trademark owned by the U.S. Green Building Council and is used by permission. Energy Star is a registered trademark of the United States EPA.

© 2026 BlueScope Buildings North America, Inc. All rights reserved. Butler Manufacturing™ is a division of BlueScope Buildings North America, Inc. Find your independent Butler Builder® at ButlerMFG.com