



STYLWALL® II FLUTED WALL SYSTEM

This wall gives the building a sense of strength and intention from the outside in. Its vertical expression adds character and depth, creating a façade that feels purposeful rather than decorative. Beneath that visual presence is a system designed to protect the building, support interior comfort and hold its performance over time. The exterior stays clean and composed, while the wall assembly reduces uncertainty during construction and long after occupancy. Integrated as part of a complete building system, it delivers confidence that the exterior will perform as reliably as it presents, year after year.

KEY BENEFITS

- **Architectural Consistency**
A composed, intentional exterior that feels unified and visually resolved from every angle.
- **Improved Thermal Performance**
Helps maintain more comfortable interior environments while supporting lower energy demand over time.
- **More Consistent Installation**
Brings clarity and control to execution, reducing disruption and helping the project progress with confidence.
- **Long-Term Durability**
Protects the exterior's appearance and integrity, preserving how the building looks and performs well into the future.

PRODUCT FEATURES

1. Fluted Exterior Profile

Distinct vertical ribs create uniform architectural shadow lines across the elevation.

2. Concealed Fastener System

Hidden attachments support clean exterior appearance.

3. Durable Finish Systems

High-performance paint coatings provide long-term durability and consistent color retention.

4. Trim and Flashing Compatibility

Designed to work with Butler trim and flashing systems for seamless integration.



SPECIFICATIONS

Panel Type	Ribbed concealed-fastener panel
Panel Profile	4" wide fluted vertical design
Panel Width	16"
Panel Gauges	24-gauge steel
Fastener Type	Concealed
Finish Options	Butler-Cote™ finish system
Insulation Options	Fiberglass blanket
Maximum Insulation Thickness	6"
Lowest Tested U-Factor	0.07
Warranty	25-year Butler-Cote finish warranty



BUTLERMFG.COM

