

DIMENSION VARIES PER PROJECT REQUIREMENT

BUTLER WALL SYSTEM WITH FLUOROPOLYMER COATING. (BUTLERIB II, SHADOWALL, STYLWALL II AND THERMAWALL)

OPTIONAL CLOSURE

BASE TRIM

BASE ANGLE

BASE CONDITIONS BY OTHERS

FOUNDATION AS REQUIRED BY LOCAL CONDITIONS

"C" OR "Z" SIDEWALL GIRT (SHOWN), GIRT SPACING VARIES AS PER EAVE HEIGHT, WIND LOAD CRITERIA AND WALL PANEL TYPE.

NOTE:
COLUMNS STRAIGHT OR TAPERED PER PROJECT REQUIREMENTS.

FIBERGLASS INSULATION AND VAPOR RETARDER

COLUMN BASE PLATES MAY BE RECESSED BELOW FINISHED FLOOR

FLOOR LINE



XX SECTION
 XX APPLICABLE TO ALL WIDESPAN FRAMES
 SCALE: 1/2" = 1'-0"

SECTION : Sidewall

WALL : TILT-UP

ROOF :

STRUCTURAL : Widespan



SIDEWALL PARTIAL HEIGHT TILT-UP WALL OFFSET AT STRUCTURAL LINE WITH METAL WALL ABOVE

BD 121

These details are for project planning and are not intended for construction. Butler Building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Please contact your nearest Butler Builder or Butler Manufacturing Company for the latest information.

©2007 Butler Manufacturing Company