

PARAPET COPING
NOT BY B.M.C.

FIELD FORM COUNTER
FLASHING

FLASHING
SUPPORT
CLIP

PANEL CLOSURE

FIBERGLASS
INSULATION
AND VAPOR
RETARDER

ENDWALL
STRUCTURAL LINE

BUTLERIB II ® ROOF
SYSTEM WITH INSULATION

ACRYLIC COATED
GALVANIZED FACTORY
PUNCHED Z-PURLIN

SKY-WEB II ® FALL
PROTECTION & INSULATION
SUPPORT SYSTEM

WALL SUPPORT
AS REQUIRED

1'-0"
MAX.
8"
MIN.

FULL HEIGHT MASONRY

CAVITY WALL WITH BRICK
AND BLOCK INSULATION,
DESIGNED TO CARRY IT'S
OWN WIND LOAD

NOTE:
COLUMNS STRAIGHT OR
TAPERED PER PROJECT
REQUIREMENTS.

COLUMN BASE PLATES
MAY BE RECESSED
BELOW FINISHED FLOOR

FLOOR LINE

FOUNDATION AS REQUIRED
BY LOCAL CONDITIONS

FLASHING AND WEEP
HOLES BY OTHERS



SECTION

APPLICABLE TO ALL WIDESPAN FRAMES
SCALE: 1/2" = 1'-0"

SECTION : Sidewall Parapet

WALL : CMU

ROOF : BUTLERIB II

STRUCTURAL : Widespan



SIDEWALL PARAPET WITH FULL HEIGHT
BRICK VENEER AND MASONRY WALL

BD 190

These details are for project planning and are not intended for construction. Butler Building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Please contact your nearest Butler Builder® or Butler Manufacturing Company for the latest information.

©2007 Butler Manufacturing Company