

PARAPET COPING  
NOT BY B.M.C.

ENDWALL  
STRUCTURAL LINE

BUTLER CMR-24 ® ROOF  
SYSTEM WITH THERMAX™ RIGID INSULATION BOARD

FIELD FORM COUNTER  
FLASHING

FLASHING  
SUPPORT  
CLIP

SEALANT

PANEL CLOSURE

1'-0"  
MAX.  
8"  
MIN.

ACRYLIC COATED  
GALVANIZED FACTORY  
PUNCHED Z-PURLIN

WALL SUPPORT  
AS REQUIRED

FULL HEIGHT MASONRY

CAVITY WALL WITH BRICK  
AND BLOCK INSULATION),  
DESIGNED TO CARRY IT'S  
OWN WIND LOAD

NOTE:  
COLUMNS STRAIGHT OR  
TAPERED PER PROJECT  
REQUIREMENTS.

COLUMN BASE PLATES  
MAY BE RECESSED  
BELOW FINISHED FLOOR

FLOOR LINE

FLASHING AND WEEP  
HOLES BY OTHERS

FOUNDATION AS REQUIRED  
BY LOCAL CONDITIONS

FIN.  
FLR.

XX SECTION

XX APPLICABLE TO ALL WIDESPAN FRAMES  
SCALE: 1/2" = 1'-0"

SECTION : Sidewall Parapet

WALL : CMU

ROOF : CMR-24

STRUCTURAL : Widespan



### SIDEWALL PARAPET WITH FULL HEIGHT BRICK VENEER AND MASONRY WALL

BD193

These details are for project planning and are not intended for construction. Butler Building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Please contact your nearest Butler Builder® or Butler Manufacturing Company for the latest information.