

PARAPET COPING
NOT BY B.M.C.

FIELD FORM COUNTER
FLASHING

FLASHING
SUPPORT
CLIP

SEALANT

PANEL CLOSURE

FIBERGLASS
INSULATION
AND VAPOR
RETARDER

ENDWALL
STRUCTURAL LINE

BUTLER MR-24 ® ROOF
SYSTEM WITH INSULATION

FACTORY PUNCHED
TRUSS PURLIN

1'-0"
MAX.
8"
MIN.

SKY-WEB II ® FALL
PROTECTION & INSULATION
SUPPORT SYSTEM

WALL SUPPORT
AS REQUIRED

FULL HEIGHT MASONRY

CAVITY WALL WITH BRICK
AND BLOCK INSULATION,
DESIGNED TO CARRY IT'S
OWN WIND LOAD

NOTE:
COLUMNS STRAIGHT OR
TAPERED PER PROJECT
REQUIREMENTS.

FLASHING AND WEEP
HOLES BY OTHERS

COLUMN BASE PLATES
MAY BE RECESSED
BELOW FINISHED FLOOR

FLOOR LINE

FOUNDATION AS REQUIRED
BY LOCAL CONDITIONS



XX SECTION

XX APPLICABLE TO ALL WIDESPAN FRAMES
SCALE: 1/2" = 1'-0"

SECTION : Sidewall Parapet

WALL : CMU

ROOF : MR-24

STRUCTURAL : Landmark 2000



SIDEWALL PARAPET WITH FULL HEIGHT BRICK VENEER AND MASONRY WALL

BD205

These details are for project planning and are not intended for construction. Butler Building products are constantly being improved; therefore, the information contained herein is subject to change without notice. Please contact your nearest Butler Builder® or Butler Manufacturing Company for the latest information.